



SafRise[®] S-Series Mast Climbers

Elevating Performance

Enhancing productivity with safe vertical access at the highest speed-to-capacity ratio available.

SafRise[®]
BY BRAND SAFWAY[™]

Aluma SAFWAY[™]

At Work For You[™]

› High speeds. Heavy loads. Maximum safety.

Nothing is out of reach with BrandSafway's SafRise® S-Series Mast Climbers.



Historic Milwaukee City Hall

"SafRise offered an unprecedented level of safety with a platform that descends in a controlled manner and offers the highest speed-to-capacity ratio on the market. It was great working with BrandSafway."

Project Manager, JP Cullen



Position crews, materials and tools for safe, optimum access to all work surfaces.

SafRise® S-Series Mast Climber Specifications

- › Motorized unit dimensions: 99" (D) x 147" (W) x 102" (H)
- › Motorized unit loading height: 56"
- › Motorized unit width: 10'
- › Motorized unit weight: 6,750 lbs.
- › Maximum platform length:
60' (single mast); 120' (twin mast)
- › Maximum payload:
8,000 lbs. (single mast); 13,000 lbs. (twin mast)
- › Maximum height of setup: 500'
- › Maximum tie spacing: 45'
- › Drive system: Rack and pinion
- › Motors: Two each – Nord 7.5 hp
- › Power requirements: 240 volt, 3 phase, 60 amp.
- › Vertical travel speed: 30 fpm
- › Safety devices: Gravity activated manual centrifugal brake 34 fpm

YOUR LOCAL EXPERT
COMMERCIAL CONSTRUCTION ACCESS SOLUTIONS

+Safety
First and Foremost

+Expertise
Industry-Leading Depth/Range

+Solutions
The Broadest Portfolio

+Productivity
Increased at Every Level

+Local
Management and Labor

Visit AlumaSafway.com
to connect with Your Local Expert.

Aluma SAFWAY™