

# SafTran<sup>®</sup> 2500 Material Hoist / Transport Platform

## Protecting the Payload

Ideal for roofing, masonry  
and restoration/renovation



**SafTran<sup>®</sup>**  
BY BRAND SAFWAY

**Aluma** > **SAFWAY<sup>™</sup>**

At Work For You<sup>™</sup>

## › Transport fragile materials easily and safely.

Low-anchor forces allow installation to most structures or scaffolds, while small footprint fits into confined spaces (10' x 10').



Dual speed motor for customizing lift can run off three-phase or single-phase power. Soft Start and Stop VFD technology keeps materials safe.

### SafTran 2500 Material Hoist / Transport Platform Specifications

- › Platform dimensions: 4'3" (W) x 7'2" (L)
- › Loading height: 16"
- › Unit weight: 1,918 lbs.
- › Maximum payload: 2,500 lbs.
- › Maximum number of people:  
Six – transport platform only
- › Travel speed: 40 fpm transport platform;  
80 fpm material hoist
- › Maximum height: 400'
- › Maximum tie spacing: 20'
- › Drive system: Rack and pinion
- › Motors: Two each – MGM 6 hp
- › Power requirements: 208 volt, 3 phase, 65 amp;  
230 volt, single phase, 65 amp
- › Safety devices: Gravity-activated manual centrifugal brake – 98 fpm tripping speed

\* Tie configuration may vary from that shown.

**YOUR LOCAL EXPERT**  
COMMERCIAL CONSTRUCTION ACCESS SOLUTIONS

**+Safety**  
First and Foremost

**+Expertise**  
Industry-Leading Depth/Range

**+Solutions**  
The Broadest Portfolio

**+Productivity**  
Increased at Every Level

**+Local**  
Management and Labor

Visit [AlumaSafway.com](https://AlumaSafway.com)  
to connect with Your Local Expert.

**Aluma SAFWAY™**